1. IDENTIFICATION OF THE SU Material Name Uses		TANCE/PREPARATION AND COMPANY/UNDERTAKING Shell Argina XL 40 Engine oil.
Product Code	:	001B3360
Manufacturer/Supplier	:	Shell Pakistan Limited Shell House Clifton 6 Chaudhry Khaliquzzaman Road 75530 Karachi Pakistan
Telephone Fax	:	(+92) 2135689525 (+92) 2135684355
Emergency Telephone Number	:	(+92) 800 74355

2. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture Description

: Highly refined mineral oils and additives.

Hazardous Components

Chemical	CAS	EINECS	Symbol(s)	R-phrase(s)	Conc.	
Identity						
Sulphurised				R53	< 3,00 %	
calcium phenate						

Additional Information	:	The highly refined mineral oil contains <3% (w/w) DMSO-
		extract, according to IP346. Refer to chapter 16 for full text of
		EC R-phrases.

3. HAZARDS IDENTIFICATION		
EC Classification	:	Not classified as dangerous under EC criteria.
Health Hazards	:	Not expected to be a health hazard when used under normal conditions. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities.
Signs and Symptoms	:	Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.
Safety Hazards	:	Not classified as flammable but will burn.
Environmental Hazards	:	Not classified as dangerous for the environment.
4. FIRST AID MEASURES		
General Information	:	Not expected to be a health hazard when used under normal

	conditions.
Inhalation	 No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
Skin Contact	 Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
Eye Contact	 Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.
Ingestion	 In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Advice to Physician	: Treat symptomatically.

5. FIRE FIGHTING MEASURES

Clear fire area of all non-emergency personnel.

Specific Hazards	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.
Suitable Extinguishing Media	:	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable Extinguishing Media	:	Do not use water in a jet.
Protective Equipment for Firefighters	:	Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space.

6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe the relevant local and international regulations.

Protective measures Clean Up Methods Additional Advice	:	Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly. Local authorities should be advised if significant spillages cannot be contained.
7. HANDLING AND STORAGE General Precautions	:	Use local exhaust ventilation if there is risk of inhalation of
		vapours, mists or aerosols. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling
		2/7

	vapour and/or mists. When handling product in drums, safety
	footwear should be worn and proper handling equipment
	should be used.
Storage	Keep container tightly closed and in a cool, well-ventilated
-	place. Use properly labelled and closeable containers. Store at ambient temperature.
Recommended Materials	For containers or container linings, use mild steel or high
	density polyethylene.
Unsuitable Materials	PVC.
Additional Information	Polyethylene containers should not be exposed to high
	temperatures because of possible risk of distortion.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

If the American Conference of Governmental Industrial Hygienists (ACGIH) value is provided on this document, it is provided for information only.

Occupational Exposure Limits

Material	Source	Туре	ppm	mg/m3	Notation
Oil mist, mineral	ACGIH	TWA(Inhala		5 mg/m3	
		ble fraction.)			

Exposure Controls Personal Protective Equipment	e level of protection and types of bending upon potential exposure sed on a risk assessment of loca propriate measures include: Ade borne concentrations. Where ma at formed, there is greater potentian centrations to be generated. rsonal protective equipment (PPI ommended national standards. (conditions. Select controls I circumstances. quate ventilation to control terial is heated, sprayed or al for airborne E) should meet
Respiratory Protection	respiratory protection is ordinaril aditions of use. In accordance wit ctices, precautions should be tal- terial. If engineering controls do accentrations to a level which is ac alth, select respiratory protection ecific conditions of use and meet eck with respiratory protective ec filtering respirators are suitable, nbination of mask and filter. Sele nbined particulate/organic gases 5°C(149 °F)].	th good industrial hygiene ken to avoid breathing of not maintain airborne dequate to protect worker equipment suitable for the ing relevant legislation. quipment suppliers. Where select an appropriate ect a filter suitable for
Hand Protection	ere hand contact with the productives approved to relevant standars: F739) made from the following table chemical protection: PVC, in the solution of a table, e.g. frequency and durability of a table, e.g. frequency and duration to the stance of glove material, glove to the solution of	rds (e.g. Europe: EN374, materials may provide neoprene or nitrile rubber a glove is dependent on of contact, chemical

	seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.
Eye Protection	: Wear safety glasses or full face shield if splashes are likely to occur.
Protective Clothing	: Skin protection not ordinarily required beyond standard issue work clothes.
Monitoring Methods	: Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.
Environmental Exposure Controls	: Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.

9. PHYSICAL AND CHEMICAL F	PROPERTIES
Appearance	: Amber. Liquid at room temperature.
Odour	: Slight hydrocarbon.
pН	: Not applicable.
Initial Boiling Point and	: > 280 °C / 536 °F estimated value(s)
Boiling Range	
Pour point	: Typical -18 °C / 0 °F
Flash point	: Typical 205 °C / 401 °F (PMCC / ASTM D93)
Upper / lower Flammability	: Typical 1 - 10 %(V) (based on mineral oil)
or Explosion limits	
Auto-ignition temperature	: > 320 °C / 608 °F
Vapour pressure	: < 0,5 Pa at 20 °C / 68 °F (estimated value(s))
Specific gravity	: Typical 0,916 at 15 °C / 59 °F
Density	: Typical 916 kg/m3 at 15 °C / 59 °F
Water solubility	: Negligible.
Solubility in other solvents	: Data not available
n-octanol/water partition	: > 6 (based on information on similar products)
coefficient (log Pow)	
Dynamic viscosity	: Data not available
Kinematic viscosity	: Typical 135 mm2/s at 40 °C / 104 °F
Vapour density (air=1)	: >1 (estimated value(s))
Evaporation rate (nBuAc=1)	
10. STABILITY AND REACTIVIT	Y
Stability	: Stable.
Conditions to Avoid	: Extremes of temperature and direct sunlight.
Materials to Avoid	: Strong oxidising agents.
Hazardous	: Hazardous decomposition products are not expected to form
Decomposition Products	during normal storage.
11. TOXICOLOGICAL INFORMA	
Basis for Assessment	: Information given is based on data on the components and the toxicology of similar products.
Acute Oral Toxicity	: Expected to be of low toxicity: LD50 > 5000 mg/kg , Rat
Acute Dermal Toxicity	: Expected to be of low toxicity: LD50 > 5000 mg/kg , Rabbit
	A/7

Acute Inhalation Toxicity	Not considered to be an inhalation hazard under normal conditions of use.	
Skin Irritation	Expected to be slightly irritating. Prolonged or repeated contact without proper cleaning can clog the pores of the resulting in disorders such as oil acne/folliculitis.	
Eye Irritation	Expected to be slightly irritating.	
Respiratory Irritation	nhalation of vapours or mists may cause irritation.	
Sensitisation	Not expected to be a skin sensitiser.	
Repeated Dose Toxicity	Not expected to be a hazard.	
Mutagenicity	Not considered a mutagenic hazard.	
Carcinogenicity	Product contains mineral oils of types shown to be non- carcinogenic in animal skin-painting studies. Highly refin mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC). O components are not known to be associated with carcin effects.	other
Reproductive and Developmental Toxicity	Not expected to be a hazard.	
Additional Information	Jsed oils may contain harmful impurities that have accumulated during use. The concentration of such imp will depend on use and they may present risks to health he environment on disposal. ALL used oil should be ha with caution and skin contact avoided as far as possible Continuous contact with used engine oils has caused sk cancer in animal tests.	and ndled

12. ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.

Acute Toxicity	Poorly soluble mixture. May cause physical fouling of aquatic organisms. Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l (to aquatic organisms) LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract. Mineral oil is not expected to cause any chronic effects
Microorganisms	to aquatic organisms at concentrations less than 1 mg/l. Data not available
Mobility	 Liquid under most environmental conditions. Floats on water. If it enters soil, it will adsorb to soil particles and will not be mobile.
Persistence/degradability	Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.
Bioaccumulation	Contains components with the potential to bioaccumulate.
Other Adverse Effects	Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.
13. DISPOSAL CONSIDERATION Material Disposal	S Recover or recycle if possible. It is the responsibility of the

```
Material Disposal
```

waste generator to determine the toxicity and physical

	properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses.
Container Disposal :	Dispose in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.
Local Legislation :	Disposal should be in accordance with applicable regional, national, and local laws and regulations.

14. TRANSPORT INFORMATION

Land (as per ADR classification): Not regulated

This material is not classified as dangerous under ADR regulations.

IMDG

This material is not classified as dangerous under IMDG regulations.

IATA (Country variations may apply)

This material is either not classified as dangerous under IATA regulations or needs to follow country specific requirements.

15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

EC Classification Chemical Inventory Status	:	Not classified as dangerous under EC criteria.
EINECS	:	All components listed or polymer
TSCA	:	exempt. All components listed.

16. OTHER INFORMATION

R-phrase(s)

R53 May cause long-term adverse effects in the aquatic environment.

MSDS Version Number	:	1.3
MSDS Effective Date	:	02/29/2012
MSDS Revisions	:	A vertical bar () in the left margin indicates an amendment from the previous version.
MSDS Distribution	:	The information in this document should be made available to all who may handle the product.

Disclaimer

: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.