1. IDENTIFICATION OF THE SU	JBS	TANCE/PREPARATION AND COMPANY/UNDERTAKING
Material Name	:	Shell Refrigeration Oil S2 FR-A 46
Uses	:	Refrigerator oil.
Product Code	:	001D8391
Manufacturer/Supplier	:	Shell Pakistan Limited Shell House Clifton 6 Chaudhry Khaliquzzaman Road 75530 Karachi Pakistan
Telephone	:	(+92) 2135689525
Fax	:	(+92) 2135684355
Emergency Telephone Number	:	(+92) 800 74355
2. COMPOSITION/INFORMATI	ON	ON INGREDIENTS
Preparation Description	:	Highly refined mineral oils and additives.
Additional Information	:	The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346.
3. HAZARDS IDENTIFICATION		
EC Classification	:	Not classified as dangerous under EC criteria.
Health Hazards Signs and Symptoms Safety Hazards Environmental Hazards	:	Not expected to be a health hazard when used under normal conditions. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. High-pressure injection under the skin may cause serious damage including local necrosis. Used oil may contain harmful impurities. Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection. Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea. Not classified as flammable but will burn. Not classified as dangerous for the environment.
4. FIRST AID MEASURES General Information Inhalation	:	Not expected to be a health hazard when used under normal conditions. No treatment necessary under normal conditions of use. If
Skin Contact	:	symptoms persist, obtain medical advice. Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent

	irritation occurs, obtain medical attention. When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop. Obtain medical attention even in the absence of apparent wounds.
Eye Contact	Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.
Ingestion	In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Advice to Physician :	Treat symptomatically. High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function. Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.

5. FIRE FIGHTING MEASURES

Clear fire area of all non-emergency personnel.

Specific Hazards	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.
Suitable Extinguishing Media Unsuitable Extinguishing Media	:	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Do not use water in a jet.
Protective Equipment for Firefighters	:	Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space.

6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe the relevant local and international regulations.

Protective measures	Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
Clean Up Methods	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.
Additional Advice	 Local authorities should be advised if significant spillages cannot be contained.

7. HANDLING AND STORAGE		
General Precautions	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used.
Storage	:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labelled and closeable containers. Storage Temperature: 0 - 50 °C / 32 - 122 °F
Recommended Materials Unsuitable Materials		For containers, or container linings use mild steel. For containers or container linings avoid PVC, polyethylene or high density polyethylene.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

If the American Conference of Governmental Industrial Hygienists (ACGIH) value is provided on this document, it is provided for information only.

Occupational Exposure Limits

Material	Source	Туре	ppm	mg/m3	Notation
Oil mist, mineral	ACGIH	TWA		5 mg/m3	
		[Mist.]			
	ACGIH	STEL		10 mg/m3	
		[Mist.]			
Exposure Contro	bls :	depending upon based on a risk Appropriate mea airborne concen mist formed, the concentrations t	potential exp assessment asures include trations. Whe re is greater o be generate	oosure condition of local circumst e: Adequate ven ere material is he potential for airb ed.	tilation to control eated, sprayed or orne
Personal Protect Equipment	ive :	Personal protec recommended r			meet n PPE suppliers.
Respiratory P	rotection :	specific conditio	e. In accorda utions should neering contro o a level whic spiratory prot ns of use and iratory protect rators are sui	nce with good in I be taken to avo ols do not mainta ch is adequate to ection equipmer I meeting releva tive equipment s itable, select an	dustrial hygiene bid breathing of ain airborne o protect worker ht suitable for the nt legislation. suppliers. Where appropriate

Hand Protection	 combined particulate/organic gases and vapours [boiling point >65°C(149 °F)]. Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.
Eye Protection	: Wear safety glasses or full face shield if splashes are likely to occur.
Protective Clothing	: Skin protection not ordinarily required beyond standard issue work clothes.
Monitoring Methods	 Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.
Environmental Exposure Controls	: Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.
9. PHYSICAL AND CHEMICAL	
	FRUFERIJES
Appearance	: Amber. Liquid at room temperature.
Appearance Odour	: Amber. Liquid at room temperature. : Slight hydrocarbon.
Appearance Odour pH	Amber. Liquid at room temperature.Slight hydrocarbon.Not applicable.
Appearance Odour	: Amber. Liquid at room temperature. : Slight hydrocarbon.
Appearance Odour pH Initial Boiling Point and Boiling Range Pour point	 Amber. Liquid at room temperature. Slight hydrocarbon. Not applicable. > 280 °C / 536 °F estimated value(s) Typical -39 °C / -38 °F
Appearance Odour pH Initial Boiling Point and Boiling Range Pour point Flash point	 Amber. Liquid at room temperature. Slight hydrocarbon. Not applicable. > 280 °C / 536 °F estimated value(s) Typical -39 °C / -38 °F Typical 218 °C / 424 °F (COC)
Appearance Odour pH Initial Boiling Point and Boiling Range Pour point Flash point Upper / lower Flammability	 Amber. Liquid at room temperature. Slight hydrocarbon. Not applicable. > 280 °C / 536 °F estimated value(s) Typical -39 °C / -38 °F
Appearance Odour pH Initial Boiling Point and Boiling Range Pour point Flash point Upper / lower Flammability or Explosion limits	 Amber. Liquid at room temperature. Slight hydrocarbon. Not applicable. > 280 °C / 536 °F estimated value(s) Typical -39 °C / -38 °F Typical 218 °C / 424 °F (COC) Typical 1 - 10 %(V)
Appearance Odour pH Initial Boiling Point and Boiling Range Pour point Flash point Upper / lower Flammability or Explosion limits Auto-ignition temperature	 Amber. Liquid at room temperature. Slight hydrocarbon. Not applicable. > 280 °C / 536 °F estimated value(s) Typical -39 °C / -38 °F Typical 218 °C / 424 °F (COC) Typical 1 - 10 %(V) > 320 °C / 608 °F
Appearance Odour pH Initial Boiling Point and Boiling Range Pour point Flash point Upper / lower Flammability or Explosion limits Auto-ignition temperature Vapour pressure	 Amber. Liquid at room temperature. Slight hydrocarbon. Not applicable. > 280 °C / 536 °F estimated value(s) Typical -39 °C / -38 °F Typical 218 °C / 424 °F (COC) Typical 1 - 10 %(V) > 320 °C / 608 °F < 0,5 Pa at 20 °C / 68 °F (estimated value(s))
Appearance Odour pH Initial Boiling Point and Boiling Range Pour point Flash point Upper / lower Flammability or Explosion limits Auto-ignition temperature Vapour pressure Density	 Amber. Liquid at room temperature. Slight hydrocarbon. Not applicable. > 280 °C / 536 °F estimated value(s) Typical -39 °C / -38 °F Typical 218 °C / 424 °F (COC) Typical 1 - 10 %(V) > 320 °C / 608 °F < 0,5 Pa at 20 °C / 68 °F (estimated value(s)) Typical 859 kg/m3 at 15 °C / 59 °F
Appearance Odour pH Initial Boiling Point and Boiling Range Pour point Flash point Upper / lower Flammability or Explosion limits Auto-ignition temperature Vapour pressure Density Water solubility n-octanol/water partition	 Amber. Liquid at room temperature. Slight hydrocarbon. Not applicable. > 280 °C / 536 °F estimated value(s) Typical -39 °C / -38 °F Typical 218 °C / 424 °F (COC) Typical 1 - 10 %(V) > 320 °C / 608 °F < 0,5 Pa at 20 °C / 68 °F (estimated value(s))
Appearance Odour pH Initial Boiling Point and Boiling Range Pour point Flash point Upper / lower Flammability or Explosion limits Auto-ignition temperature Vapour pressure Density Water solubility n-octanol/water partition coefficient (log Pow)	 Amber. Liquid at room temperature. Slight hydrocarbon. Not applicable. > 280 °C / 536 °F estimated value(s) Typical -39 °C / -38 °F Typical 218 °C / 424 °F (COC) Typical 1 - 10 %(V) > 320 °C / 608 °F < 0,5 Pa at 20 °C / 68 °F (estimated value(s)) Typical 859 kg/m3 at 15 °C / 59 °F Negligible. > 6 (based on information on similar products)
Appearance Odour pH Initial Boiling Point and Boiling Range Pour point Flash point Upper / lower Flammability or Explosion limits Auto-ignition temperature Vapour pressure Density Water solubility n-octanol/water partition coefficient (log Pow) Kinematic viscosity	 Amber. Liquid at room temperature. Slight hydrocarbon. Not applicable. > 280 °C / 536 °F estimated value(s) Typical -39 °C / -38 °F Typical 218 °C / 424 °F (COC) Typical 1 - 10 %(V) > 320 °C / 608 °F < 0,5 Pa at 20 °C / 68 °F (estimated value(s)) Typical 859 kg/m3 at 15 °C / 59 °F Negligible. > 6 (based on information on similar products) Typical 46 mm2/s at 40 °C / 104 °F
Appearance Odour pH Initial Boiling Point and Boiling Range Pour point Flash point Upper / lower Flammability or Explosion limits Auto-ignition temperature Vapour pressure Density Water solubility n-octanol/water partition coefficient (log Pow)	 Amber. Liquid at room temperature. Slight hydrocarbon. Not applicable. > 280 °C / 536 °F estimated value(s) Typical -39 °C / -38 °F Typical 218 °C / 424 °F (COC) Typical 1 - 10 %(V) > 320 °C / 608 °F < 0,5 Pa at 20 °C / 68 °F (estimated value(s)) Typical 859 kg/m3 at 15 °C / 59 °F Negligible. > 6 (based on information on similar products) Typical 46 mm2/s at 40 °C / 104 °F > 1 (estimated value(s))
Appearance Odour pH Initial Boiling Point and Boiling Range Pour point Flash point Upper / lower Flammability or Explosion limits Auto-ignition temperature Vapour pressure Density Water solubility n-octanol/water partition coefficient (log Pow) Kinematic viscosity Vapour density (air=1)	 Amber. Liquid at room temperature. Slight hydrocarbon. Not applicable. > 280 °C / 536 °F estimated value(s) Typical -39 °C / -38 °F Typical 218 °C / 424 °F (COC) Typical 1 - 10 %(V) > 320 °C / 608 °F < 0,5 Pa at 20 °C / 68 °F (estimated value(s)) Typical 859 kg/m3 at 15 °C / 59 °F Negligible. > 6 (based on information on similar products) Typical 46 mm2/s at 40 °C / 104 °F > 1 (estimated value(s)) Data not available
Appearance Odour pH Initial Boiling Point and Boiling Range Pour point Flash point Upper / lower Flammability or Explosion limits Auto-ignition temperature Vapour pressure Density Water solubility n-octanol/water partition coefficient (log Pow) Kinematic viscosity Vapour density (air=1) Evaporation rate (nBuAc=1)	 Amber. Liquid at room temperature. Slight hydrocarbon. Not applicable. > 280 °C / 536 °F estimated value(s) Typical -39 °C / -38 °F Typical 218 °C / 424 °F (COC) Typical 1 - 10 %(V) > 320 °C / 608 °F < 0,5 Pa at 20 °C / 68 °F (estimated value(s)) Typical 859 kg/m3 at 15 °C / 59 °F Negligible. > 6 (based on information on similar products) Typical 46 mm2/s at 40 °C / 104 °F > 1 (estimated value(s)) Data not available
Appearance Odour pH Initial Boiling Point and Boiling Range Pour point Flash point Upper / lower Flammability or Explosion limits Auto-ignition temperature Vapour pressure Density Water solubility n-octanol/water partition coefficient (log Pow) Kinematic viscosity Vapour density (air=1) Evaporation rate (nBuAc=1) 10. STABILITY AND REACTIVIT Stability Conditions to Avoid	 Amber. Liquid at room temperature. Slight hydrocarbon. Not applicable. > 280 °C / 536 °F estimated value(s) Typical -39 °C / -38 °F Typical 218 °C / 424 °F (COC) Typical 1 - 10 %(V) > 320 °C / 608 °F < 0,5 Pa at 20 °C / 68 °F (estimated value(s)) Typical 859 kg/m3 at 15 °C / 59 °F Negligible. > 6 (based on information on similar products) Typical 46 mm2/s at 40 °C / 104 °F > 1 (estimated value(s)) Data not available Y Stable. Extremes of temperature and direct sunlight.
Appearance Odour pH Initial Boiling Point and Boiling Range Pour point Flash point Upper / lower Flammability or Explosion limits Auto-ignition temperature Vapour pressure Density Water solubility n-octanol/water partition coefficient (log Pow) Kinematic viscosity Vapour density (air=1) Evaporation rate (nBuAc=1) 10. STABILITY AND REACTIVIT Stability Conditions to Avoid Materials to Avoid	 Amber. Liquid at room temperature. Slight hydrocarbon. Not applicable. > 280 °C / 536 °F estimated value(s) Typical -39 °C / -38 °F Typical 218 °C / 424 °F (COC) Typical 1 - 10 %(V) > 320 °C / 608 °F < 0,5 Pa at 20 °C / 68 °F (estimated value(s)) Typical 859 kg/m3 at 15 °C / 59 °F Negligible. > 6 (based on information on similar products) Typical 46 mm2/s at 40 °C / 104 °F > 1 (estimated value(s)) Data not available Y Stable. Extremes of temperature and direct sunlight. Strong oxidising agents.
Appearance Odour pH Initial Boiling Point and Boiling Range Pour point Flash point Upper / lower Flammability or Explosion limits Auto-ignition temperature Vapour pressure Density Water solubility n-octanol/water partition coefficient (log Pow) Kinematic viscosity Vapour density (air=1) Evaporation rate (nBuAc=1) 10. STABILITY AND REACTIVIT Stability Conditions to Avoid	 Amber. Liquid at room temperature. Slight hydrocarbon. Not applicable. > 280 °C / 536 °F estimated value(s) Typical -39 °C / -38 °F Typical 218 °C / 424 °F (COC) Typical 1 - 10 %(V) > 320 °C / 608 °F < 0,5 Pa at 20 °C / 68 °F (estimated value(s)) Typical 859 kg/m3 at 15 °C / 59 °F Negligible. > 6 (based on information on similar products) Typical 46 mm2/s at 40 °C / 104 °F > 1 (estimated value(s)) Data not available Y Stable. Extremes of temperature and direct sunlight.

Basis for Assessment	: Information given is based on data on the components and the toxicology of similar products.
Acute Oral Toxicity	: Expected to be of low toxicity: LD50 > 5000 mg/kg , Rat
Acute Dermal Toxicity	: Expected to be of low toxicity: LD50 > 5000 mg/kg , Rat
Acute Inhalation Toxicity	: Not considered to be an inhalation hazard under normal
Acute initialation Toxicity	conditions of use.
Skin Irritation	: Expected to be slightly irritating. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.
Eye Irritation	: Expected to be slightly irritating.
Respiratory Irritation	: Inhalation of vapours or mists may cause irritation.
Sensitisation	: Not expected to be a skin sensitiser.
Repeated Dose Toxicity	: Not expected to be a hazard.
Mutagenicity	: Not considered a mutagenic hazard.
Carcinogenicity	 Product contains mineral oils of types shown to be non- carcinogenic in animal skin-painting studies. Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC). Other components are not known to be associated with carcinogenic effects.
Reproductive and Developmental Toxicity	: Not expected to be a hazard.
Additional Information	: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible. High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

12. ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.

Acute Toxicity	Poorly soluble mixture. May cause physical fouling of aquatic organisms. Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l (to aquatic organisms) (LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract). Mineral oil is not expected to cause any chronic effects to aquatic organisms at concentrations less than 1 mg/l.
Mobility	Liquid under most environmental conditions. Floats on water. If it enters soil, it will adsorb to soil particles and will not be mobile.
Persistence/degradability	Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.
Bioaccumulation	Contains components with the potential to bioaccumulate.
Other Adverse Effects	Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical

	ozone creation potential or global warming potential.
13. DISPOSAL CONSIDERATIONS	
Material Disposal :	Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses.
Container Disposal	Dispose in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.
Local Legislation	Disposal should be in accordance with applicable regional, national, and local laws and regulations.

ozone creation potential or global warming potential.

14. TRANSPORT INFORMATION

Land (as per ADR classification): Not regulated This material is not classified as dangerous under ADR regulations.

IMDG

This material is not classified as dangerous under IMDG regulations.

IATA (Country variations may apply)

This material is not classified as dangerous under IATA regulations.

15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

	Not classified as dangerous under EC criteria.
Local Inventories	
EINECS :	All components listed or polymer
	exempt.
TSCA :	All components
	listed.

16. OTHER INFORMATION

MSDS Version Number	:	1.0
MSDS Effective Date	:	07/28/2010
MSDS Revisions	:	A vertical bar () in the left margin indicates an amendment from the previous version.
MSDS Distribution	:	The information in this document should be made available to all who may handle the product.

Disclaimer : This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.